

# MHDPPK Series

## Plastic Hood & D-Sub Connector Kit | Stamped & Formed



### Description

- Black plastic Clamshell design
- Quick Snap together locking system
- Cable entry, Top 90°
- Will accommodate up to 9.0mm diameter cable
- Cable clamp is secured with 2 screws
- 4-40UNC Jackscrews, with plastic caps
- D-Sub Connector with stamped contacts, gold plated contacts, Tin plated solder buckets

### The Kit Contains:

Male or Female Connector with Solder Buckets	x1
Backshell halves	x2
4-40 Jackscrews	x2
Plastic Strain Relief	x1
Metal Strain Relief Clamp with screws	x1

### Specification

#### Hood:

- No Contacts: 9, 15, 25
- Kit Type: D-Sub Connector Kit
- Housing Material: Nickel Plated Zinc
- Cable Entry: Straight, 90 degree
- Cable OD: Up to 11.5 mm

#### D-Sub Connector:

- Voltage Rating: 250V
- Current Rating: 3 Amps
- Contact Resistance: 25mA Max
- Insulation Resistance: 1000M  $\Omega$
- Operating Temperature: -55°C to 105°C
- Shell: Tin Plated Steel
- Insulator Material: Glass Filled Polyester
- Flammability Rating: UL94 V-0
- Contact Material: Copper Alloy
- Contact Plating: Selective Gold over Nickel, Solder bucket: Tin plated

